

**S20T**

S20TR2-SLRA8-35

一体型 3°


刚性值 (μm / kgf)

ΦP.218

S

平衡值 (N)

ΦP.221



**■注意事项**

- 刀具安装…插入刀具时,请务必将刀具插入比安全记号更深的位置。

最短夹持长度  
刀具最大插入长度

**SUGINO**

V9/NSV9/H5/H7/H9



壁厚

**HEATROBO电磁 1200S (HRD-01S-230AS)**  
电磁式加热器对应表

[○] 可加热 [×] 不可加热

コード	φD	φC	t	L	M	L <sub>1</sub>	φC <sub>1</sub>	φC <sub>2</sub>	H	h	Kg	N	S	缩略图	
<b>S20TR2-SLSA 3-40</b> -60	3	6	1.5	40	22	5.5	8.3	20	9	46	0.1	0.4	4.6	○	1
				60	42		10.4			66				9.2	2
<b>S20TR2-SLSA3.175-40</b> -60	3.175	6.175	1.5	40	22	5.5	8.5	20	9	46	0.1	0.4	4.4	○	3
				60	42		10.6			66				8.8	4
<b>S20TR2-SLSA 4-40</b> -60	4	7	1.5	40	22	5.5	9.3	20	12	46	0.1	0.4	3.6	○	5
				60	42		11.4			66				7.2	6
<b>S20TR2-SLSA 5-40</b> -60	5	8	1.5	40	22	5.5	10.3	20	15	46	0.1	0.4	2.8	○	7
				60	42		12.4			66				5.8	8
<b>S20TR2-SLSA 6-60</b> -SLRA 6-35	6	9	1.5	60	42	5.5	13.4	20	18	66	0.1	0.5	4.7	○	9
		12	3	35	19.6		2.9			14.1				—	46
<b>S20TR2-SLRA 8-35</b>	8	14	3	35	19.6	2.9	16.1	—	20	51	0.1	0.4	0.9	×	11
<b>S20TR2-SLRA10-35</b>	10	16	3	35	19.6	2.9	18.1	—	20	51	0.1	0.5	0.8	×	12
<b>S20TR2-SLRA12-45</b>	12	20	4	45	32.5	—	23.4	—	30	51	0.2	0.6	0.8	×	13

S=1:4

**φ3**

**S20TR2-SLSA3-40** (No.1) t=1.5, 4.6  
**S20TR2-SLSA3-60** (No.2) t=1.5, 9.2  
**S20TR2-SLSA3.175-40** (No.3) t=1.5, 4.4  
**S20TR2-SLSA3.175-60** (No.4) t=1.5, 8.8

**φ4**

**S20TR2-SLSA4-40** (No.5) t=1.5, 3.6  
**S20TR2-SLSA4-60** (No.6) t=1.5, 7.2

**φ5**

**S20TR2-SLSA5-40** (No.7) t=1.5, 2.8  
**S20TR2-SLSA5-60** (No.8) t=1.5, 5.8

**φ6**

**S20TR2-SLSA6-60** (No.9) t=1.5, 4.7

**φ8**

**S20TR2-SLRA6-35** (No.10) t=3, 1.1  
**S20TR2-SLRA8-35** (No.11) t=3, 0.9

**φ10**

**S20TR2-SLRA10-35** (No.12) t=3, 0.8

**φ12**

**S20TR2-SLRA12-45** (No.13) t=4, 0.8